

NEXUS

ACOUSTICAL WALL PANEL

Nexus Panels are a custom manufactured wall panel system. Nexus can be built in standard sizes such as 4' X 6' or 4' X 8' or be manufactured in any custom size catering to your design needs.

WALLS

FEATURES

- Available in 3 different finishes
- Multiple thickness's available 1" (25mm), 2" (50mm), 3" (76mm), 4" (101mm)
- 4 Different impact resistant layers available

BENEFITS


- Highly customizable to your design
- High sound absorption
- Excellent resistance to impact in abusive environments

AVAILABLE FINISHES



COATED FINISH

Smooth monolithic finish in our standard AURA White or any custom color!



FABRIC

Many fabrics, vinyls and felt available from Guilford of Maine, FilzFelt, Knoll, Design Tex, Maharam, Carnegie, Omnova and many more.

AVAILABLE IMPACT LAYERS

STANDARD

Panel Composition
 . Medium Density Fiberglass Core 6-7 PCF
 . Choice of finish
Recommended Use:
 . Areas where panels are not likely to receive abuse or impact.

HIGH IMPACT


Panel Composition
 . Medium Density Fiberglass Core 6-7 PCF
 . High Density Fiberglass Face (HDF)
 . Choice of finish
Recommended Use:
 . Added protection to panels
 . Areas where slight abuse or impact may occur
 . Tackability
 Adds 1/8" (3mm)

HIGH IMPACT ULTIMATE

Panel Composition
 . Medium Density Fiberglass Core 6-7 PCF
 . High Density Sorlin
 . Choice of finish
Recommended Use:
 . Gymnasium

NOVA

Panel Composition
 . Medium Density Fiberglass Core 6-7 PCF
 . Perforated Co-polymer
 . Choice of finish
Recommended Use:
 . Gymnasium




FINTO FINISH

High resolution printed wood grain fabric available in many species, and shades.

GENERAL DATA

- Noise reduction Coefficient (NRC) as tested to ASTM C423 in our 1" meets a 0.90 NRC
- Noise reduction Coefficient (NRC) as tested to ASTM C423 in our 2" meets a 1.05 NRC
- Noise reduction Coefficient (NRC) as tested to ASTM C423 in our 3" + meets a 1.30 NRC
- Fire Performance as tested to ASTM E84 meets a class "A" fire rating w/a Flame spread index of 0 and a smoke Development index of 10
- Our Standard "AURA White" in the coating system has been tested to a ASTM E1477-9a and has a rating of 90% light Reflectance

EDGE DETAILS AVAILABLE




TECHNICAL DATA

| FINISH | THICKNESS | FIRE RATING | NRC | CAC | CORE DENSITY | LEED | WARRANTY |
|--------|-----------|-------------|------|-----|--------------|--|----------|
| COATED | 1" (25mm) | CLASS A | 0.90 | N/A | 6-7 PCF | HPD's, EPD's, EDS,CDPH, Recycled Content | 2 YEA RS |
| | 2" (50mm) | CLASS A | 1.05 | N/A | 6-7 PCF | HPD's, EPD's, EDS,CDPH, Recycled Content | 2 YEARS |
| FABRIC | 1" (25mm) | CLASS A | 0.90 | N/A | 6-7 PCF | HPD's, EPD's, EDS,CDPH, Recycled Content | 2 YEARS |
| | 2" (50mm) | CLASS A | 1.05 | N/A | 6-7 PCF | HPD's, EPD's, EDS,CDPH, Recycled Content | 2 YEARS |
| LOHA | 1" (25mm) | CLASS A | 0.90 | N/A | 6-7 PCF | HPD's, EPD's, EDS,CDPH, Recycled Content | 2 YEARS |
| | 2" (50mm) | CLASS A | 1.05 | N/A | 6-7 PCF | HPD's, EPD's, EDS,CDPH, Recycled Content | 2 YEARS |
| FINTO | 1" (25mm) | CLASS A | 0.90 | N/A | 6-7 PCF | HPD's, EPD's, EDS,CDPH, Recycled Content | 2 YEARS |
| | 2" (50mm) | CLASS A | 1.05 | N/A | 6-7 PCF | HPD's, EPD's, EDS,CDPH, Recycled Content | 2 YEARS |


2" (51mm) thick panels have a NRC of up to 1.05

available in 3" and 4" NRC of up to 1.3


AVAILABLE MOUNTING SYSTEMS CEILING MOUNT & WALL MOUNT




Hook & loop
Velcro



MAGNET



Direct Mount
Wall Z-Clip



Impaling Clip

LEED DATA

MR - Materials and Resources

- 1 Point - Building Product Disclosure and Optimization - EPD
- 1 Point - Building Product Disclosure and Optimization - HPD
- 1 Point - Leadership Extraction Practices - Recycled Content

IEQ-Indoor Environmental Quality(Prerequisite)

- 1-2 Point - Interior Lighting/Surface Reflectivity (AURA WHITE FINISH) E1477-9
- 1-3 Points - Low Emitting Materials (CDPH) Must use our "G" Series Core

